

To cite this article (example in APA citation format):

Jiménez-Rivero, A., & García-Navarro, J. (2017). Best practices for the management of end-of-life gypsum in a circular economy. *Journal of Cleaner Production*, 167, 1335-1344.
<https://doi.org/10.1016/j.jclepro.2017.05.068>

Post-print version

Best practices for the management of end-of-life gypsum in a circular economy

Ana Jiménez-Rivero ^{a, *}, Justo García-Navarro ^a

^a Universidad Politécnica de Madrid, Research Group Sustainability in Construction and Industry giSCI-UPM, ETSIAAB, Av. Puerta de Hierro, 2-4, 28040 Madrid, Spain

* Corresponding author. Tel.: +34 91 336 58 65; fax: +34 91 336 36 88
E-mail address: ana.jimenez@upm.es

Abstract

While gypsum can effectively be recycled, most gypsum waste (GW) is currently landfilled in the European Union. In order to achieve higher recovery rates and promote a closed-loop supply chain, it is necessary that stakeholders can implement best practices, in particular from waste production to waste processing, processes that are part of the end-of-life (EoL) stage. In this stage, waste production cannot be reduced, and therefore the priority should be to appropriately collect and recover EoL products. The aim of the paper is to investigate best practices for the management of EoL gypsum in a circular economy. To achieve this, best practices for the management of EoL construction products are selected from the literature, adapted to the case of EoL gypsum and subjected to stakeholder consultation. Results revealed significant differences in the waste management practices between two target groups: gypsum recycling and non-gypsum recycling countries. It is concluded that three best practices are fundamental to promote a circular economy for gypsum products: on-site segregation of GW, clear waste acceptance criteria and clear recycled gypsum quality criteria.

Keywords: construction sector; deconstruction; resource efficiency; circular economy; lean value chain; secondary raw materials.

Highlights

- Practices for closing the loop of gypsum products in a circular economy are identified
- Stakeholders' views on best practices are explored
- Three best practices are proposed as fundamental to enable gypsum recycling.

1. Introduction

The destination of end-of-life (EoL) construction products is diverse (re-use, recycling, other recovery or disposal) and those treatments that demonstrate the best environmental performance should be encouraged (European Parliament and the Council of the European Union, 2008). These EoL products (also known as demolition and renovation waste) are increasingly generated in the European Union (EU), as the building stock increases and buildings approach the end of their service life (Buildings Performance Institute Europe (BPIE), 2011). Therefore, building products reach the EoL stage and become EoL products. It is estimated that 46%



of the construction and demolition (C&D) waste produced in the EU is re-used or recycled (European Commission (DG ENV), 2011). For the case of EoL products alone, EU data is not available. In all cases, recycling involves avoiding losing resources and achieving the 70% recovery target by 2020 (European Parliament and the Council of the European Union, 2008). However, more than half of the potential raw materials resources are either incinerated or dumped in landfills (European Commission (DG ENV), 2011), which entails a loss of resources. In order to change this current situation, alternatives to the common EoL practices should be considered and assessed, in order to identify the ones that close the material loop while improving the environmental performance (Silvestre et al., 2014).

EoL construction products are mainly composed of inert products (e.g. concrete, ceramic), along with small quantities of non-inert ones, such as wood, packaging waste and gypsum waste (GW). In particular, GW makes up between 0.2% and 0.4% by weight of the total C&D waste composition (European Commission (DG ENV), 2011). Although gypsum comprises a small proportion of the total waste, gypsum landfilling commonly entails hydrogen sulphide and higher greenhouse gas emissions (Jiménez Rivero et al., 2016). On the contrary, gypsum recycling contributes to achieve the 70% recovery target above mentioned.

Adopted practices by stakeholders at the EoL stage commonly determine the fate of EoL gypsum products. The EoL stage (CEN, 2012) of gypsum for recycling starts with deconstruction (or selective demolition, as opposed to the conventional un-selective demolition), transport of the post-consumer GW and processing. Therefore, various stakeholders should cooperate in this stage (e.g. contractors, waste collectors, gypsum recyclers and manufacturers). For example, inadequate practices at the deconstruction site may convert recyclable GW into a non-recyclable material (i.e. non-compliance with the waste acceptance criteria, see Section 2.15).

The notion of best practices has been used by many authors and in many contexts. Traditionally, best practices have commonly focused on the quality and competitiveness of business processes (Heibeler et al., 1998; Szulanski, 1996; Ward, 1997; Zairi, 1997). Best practices are currently applied in other contexts too, such as new products development, ecosystem restoration, recycling networks and waste management improvement (Barczak and Kahn, 2012; Eleftheriadis and Myklebust, 2015; Farel et al., 2013; Kurdve et al., 2014; Mansar and Reijers, 2005; Rose et al., 2015; Rossi et al., 2012; Villoria Saez et al., 2013). Increased knowledge on the best practices for EoL gypsum may lead to appropriate stakeholders' decisions for promoting recycling. Moreover, sharing of best practices is considered vital for success (Zutshi and Creed, 2014).

A number of recent studies on C&D waste have thoroughly analysed measures for successful management strategies (Begum et al., 2009; Poon et al., 2001; Tam, 2008; Villoria Saez et al., 2013; Wang et al., 2010). More recently, the best practice of prefabrication implementation was evaluated by Tam et al. (2014), as a strategy to induce waste reduction. However, little attention has been paid to the peculiarities of different waste streams (e.g. non-inert non-hazardous waste such as gypsum) and the EoL stage (e.g. renovation and deconstruction works). In this stage, strategies to prevent or reduce EoL products cannot be applied and thus the collection for re-use or recycling should be prioritized. Therefore, this study focuses on the EoL stage, from deconstruction to the production of quality secondary raw materials, of a non-inert waste fraction: gypsum. This work proposes a set of best practices for the management of EoL gypsum in a circular economy.

The concept of circular economy involves principles from several schools of thought, such as the cradle to cradle design (McDonough and Braungart, 2002), biomimicry (Benyus, 2002) and the performance economy (Stahel, 2010). The concept can be summarized in three principles for action, related to the preservation of natural resources, the optimization of resource yields and the effectiveness of the system (Ellen MacArthur Foundation, 2016). In accordance with them particular actions are to be taken in each step of the value chain, i.e. production, consumption, waste management and production of secondary raw materials, as formulated in the EU Action Plan for the Circular Economy (European Commission, 2015). The scope of this paper is limited to the steps "waste management" and "production of secondary raw materials". To this end, a set of 23 best practices were outlined (see Section 2) and subjected to stakeholder consultation (as described in Section 3). Finally, data analysis of the survey results yielded a selection of the fundamental practices at EU level. It should be noted that best practices in this study are designed to operate at the micro-level (i.e. a particular deconstruction-recycling value chain), in contrast to factors influencing the fate of GW at EU or country level

(i.e. at the macro level). On the one hand, the already identified factors provide a framework for decision-makers to improve the functioning of the gypsum value chain (Jiménez-Rivero and García-Navarro, 2017). On the other hand, the best practices studied here aim to guide stakeholders of the deconstruction-recycling value chain (construction agents, recycling agents and manufacturers) towards embracing a circular economy for EoL gypsum.

2. Selected best practices for the management of EoL gypsum in a circular economy

Best practices for closing the loop of EoL construction products were identified from the literature, and adapted to the case of gypsum when required. Additional practices were defined as a result of findings from the European Life+ Gypsum to Gypsum (GtoG) project “From production to recycling: a circular economy for the European gypsum Industry with the demolition and recycling Industry” (GtoG project, 2013), which framed this investigation (see Table 1). The practices are grouped under four codes: deconstruction (DE), recycling (RE), manufacturing (MA) and general (GE). The code assigned to each practice includes these abbreviations (e.g. best practice DE3 belongs to the category “Deconstruction”). It is worth noting that some of the practices are interrelated and benefit each other. For example, when a precise site waste management plan (DE4) operates, the number and size of containers needed (DE9) should be planned, and the number of round-trips from deconstruction to the recycling plant are likely to be minimized (DE10). These connections are explained, along with the description of each practice, in sub-sections 2.1-2.23 below.

Table 1. Selected practices for the management of EoL gypsum in a circular economy

Code	Best practice	Source
DE1	Plan coordination and review meetings	Faniran and Caban, (1998), Formoso et al. (2002), Lönngren, Rosenkranz, & Kolbe (2010), Lu and Yuan (2010), Villoria Saez et al. (2013), Antink et al. (2014) and Calvo, Varela-Candamio, Novo-Corti (2014)
DE2	Appointment of a worker responsible for the follow-up of the waste management	Lu and Yuan (2010) and Villoria Saez et al. (2013)
DE3	Implement an effective pre-deconstruction audit	Chini and Bruening, (2003), Hurley (2003), Delgado et al. (2009), Singapore Government, HISER project - H2020 under agreement No. 642085
DE4	Draft and implement a precise site waste management plan (SWMP)	WRAP (2011) and Ajayi et al. (2015)
DE5	Train workers concerning gypsum products dismantling, as well as sorting and storing of GW	Shen and Tam (2002), Tam (2008), Begum et al. (2009) Lu and Yuan (2010) and Villoria Saez et al. (2013)
DE6	Appointment of trained workers	WRAP (2007), CIB (2014) and Ajayi et al. (2015)
DE7	Perform an on-site segregation of GW	Poon et al. (2001), Tam (2008), del Río Merino, Izquierdo Gracia, and Weis Azevedo (2010), Lu and Yuan (2010), Wang et al.(2010) and Villoria Saez et al. (2013) and Ajayi et al. (2015)
DE8	Effective planning of GW capture systems	WRAP (2007)
DE9	Plan number and size of containers needed	Llatas (2011), del Río Merino, Izquierdo Gracia, and Weis Azevedo (2010) and Villoria Saez et al. (2013)
DE10	Minimize number of roundtrips to recycling	GtoG project (2015c)
DE11	Perform GW traceability, from source to final destination	Lu, Huang, and Li (2011), Deloitte (2015), Wilson et al. (2014)
RE1	Recycling plant or warehouse strategically located	Beamon and Fernandes (2004), Kourmpanis et al. (2008), Banias et al. (2010), Calvo, Varela-Candamio, Novo-Corti (2014)
RE2	Have an adequate warehouse for GW and RG storage	GtoG project (2015c)
RE3	Operate a quality management system	Council of the European Union (2011); Villanueva and Eder (2011), EC (2012) and EC (2013)

RE4	Set clear waste acceptance criteria	Tukker et al. (1999), Delgado et al. (2009), Agrela et al. (2011), WRAP and BSI (2013)
RE5	Perform effective sorting operations prior to GW processing	GtoG project (2015c)
RE6	Prepare a schedule of sampling and test frequencies for each quality criteria parameter	Villanueva and Eder (2011); WRAP and BSI (2013)
RE7	Agree suitable supply contracts between recyclers and manufacturers	WRAP and BSI (2013), GtoG project, (2015c)
MA1	Set clear RG quality criteria	Bundesverband der Gipsindustrie e.V. (2013), WRAP and BSI (2013)
MA2	Promote plasterboard take-back schemes	AEA Technology Plc (2006), WRAP (2006) and Nnorom and Osibanjo (2008)
MA3	Set a RG reincorporation target	GtoG project (2015c)
GE1	Address the end-of-waste (EoW) status	Villanueva et al. (2010), Delgado et al. (2009), The Council of the European Union (2011), The European Commission (2012), The European Commission (2013), Hjelmar et al. (2013)
GE2	Availability of suitable close-top skips	GtoG project (2015c)

DE: deconstruction; RE: recycling; MA: manufacturing; GE: general. GW: gypsum waste; RG: recycled gypsum

2.1. Plan coordination and review meetings (DE1)

Coordination among agents has been traditionally considered during the design (Formoso et al., 2002), from design to construction (Faniran and Caban, 1998; Lu and Yuan, 2010), and from design to use stage (Lönngren et al., 2010). Here we propose regular communication among agents involved in the EoL stage. Such coordination allows revision of coordination measures, identification of problems to be overcome, discussion of procedures and schedules as well as requirements for recovery operations, in compliance with the SWMP, where it exists (see DE4). Antink et al. (2014) warns about the lack of coordination among agents in the construction sector, which is also identified by Calvo et al. (2014) as one of the main social barriers for C&D waste management.

2.2. Appointment of a worker responsible for the follow-up of the waste management (DE2)

The follow-up of waste management typically includes on-site C&D waste supervision, such as periodic checks on storage areas or the use of containers (Lu and Yuan, 2010; Villoria Saez et al., 2013). Moreover, traceability checks should be encouraged (e.g. delivery notes from source to final destination). GW containers should be covered at the end of the day in order to reduce potential moisture and impurities.

2.3. Implement an effective pre-deconstruction audit (DE3)

An accurate (i.e. minimum deviation between waste foreseen and generated) pre-deconstruction audit, also referred as pre-demolition inventory or building inventory, should describe the waste fractions to be generated (e.g. type, opportunities to reuse or recycle), amount, location and expected recovery rates. When properly prepared, the pre-deconstruction audit becomes a planning tool for the deconstruction work (Delgado et al., 2009, HISER project - H2020 under agreement No. 642085, n.d.; Singapore Government, n.d.). In this way, the uncertainty on what systems will be found when dismantling is reduced (Delgado et al., 2009). Such waste prediction will set the basis for the development of a sound site waste management plan (see DE4), which in turn will result in increased recovery options of materials, along with the potential cost savings associated. Examples of existing site waste management tools include the Demolition Protocol in Singapore (Singapore Government, n.d.) and the Site Methodology to Audit Reduced Target Waste (SMARTWaste) in the UK.

2.4. Draft and implement a precise site waste management plan (SWMP) (DE4)

A typical SWMP involves waste prevention and management strategies before, during and after the construction works (Ajayi et al., 2015). This document can be applied in any construction, excavation or demolition activity (e.g. new construction, maintenance, deconstruction, excavation, alteration, civil engineering and decoration works). Focusing on EoL products, an outstanding SWMP should go beyond

legislative compliance and contain a precise waste forecast (which can be known after Implementing an effective pre-deconstruction audit, see DE3), plan how to reuse and then recover the forecasted waste (i.e. specify waste carriers, plan waste destinations, waste management and recovery actions), implement and monitor the plan (i.e. record actual waste movements) (Ministerio de la Presidencia, 2008; WRAP, 2011). The document should be updated during the course of the project, recording how waste is actually managed and the deviation with the waste foreseen. Currently, these plans are mainly prepared to fulfil legal requirements (e.g. in Spain it is regulated by the Royal Decree 105/2008) or the requirements of an evaluation tool (e.g. BREEAM or LEED).

2.5. Train workers concerning gypsum products dismantling, as well as sorting and storing of GW (DE5)

On the one hand, the development of C&D waste management awareness is a lengthy process that requires vocational worker's training and education (Lu and Yuan, 2010). On the other hand, skills on dismantling can be easily learned (essentially deconstruction follows the reverse order of construction; for further insight into deconstruction see CIB, 2000). Providing in-house and periodic training can be an effective measure to enrich waste management knowledge training for different levels of employees (Shen and Tam, 2002; Tam, 2008). Begum et al. (2009) found that the participation in waste management training programmes cause positive attitudes towards waste management.

2.6. Appointment of trained workers (DE6)

Trained workers in waste dismantling, sorting and storing (see best practice above, DE5) should be appointed for proper dismantling, source separation and subsequent storage. By way of illustration, noticeable time savings are achieved when placing GW straight into the containers that will be collected by the waste carrier, rather than stockpiling the waste first and collect it later on (WRAP, 2007). In any case, workers dedicated to sorting operations were found to successfully impact recycling operations (Ajayi et al., 2015).

2.7. Perform on-site segregation of GW (DE7)

On-site segregation, also known as on-site sorting, source separation or source segregation, refers to the process of sorting different EoL products after dismantling, and should be followed by separate collection. On-site segregation of C&D materials has been largely studied as a waste management measure (Poon et al. 2001, Tam, 2008; del Río Merino et al., 2010; Lu and Yuan, 2010; Villoria Saez et al., 2013; Wang et al., 2010) and as a waste management strategy to divert waste from landfills (Ajayi et al., 2015). In particular, on-site segregation of EoL gypsum allows minimum levels of impurity and therefore the generation of greater amounts of recyclable GW. If the waste owner cannot perform this operation (e.g. due to the lack of physical space), a transfer station, where segregation can be applied, should be used.

2.8. Effective planning of GW capture systems (DE8)

Effective planning and implementation of GW capture systems limits manual handling operations (see WRAP (2007) for schematics of different capture systems such as the chute to skip system and the hoist and bag system). Their successful use depends on peculiarities of each construction site. These peculiarities should be carefully examined in order to design adequate systems (WRAP, 2007).

2.9. Plan number and size of containers needed (DE9)

In order to plan the needed containers, the estimated volume of waste, calculated in the pre-deconstruction audit (see DE3) and SWMP (see DE4) prior to commence of the deconstruction works, is valuable information. From that estimation, the number and size of containers considering the amount of storage space needed can be planned for an efficient collection frequency (Llatas, 2011). In this way, GW storage and roundtrips (see DE10) to the final destination are optimized, at the same time that recycling and recovery options are increased. This entails economic and time savings.

2.10. Minimize number of roundtrips to recycling (DE10)

The number of roundtrips can be minimized when coordination (see DE1) and traceability (see DE2 and DE11) measures are followed, commonly framed in the waste management plan (see DE4). The frequency for containers' collection should be planned in advance, ensuring that, whenever possible, only full containers are transported whilst preventing containers from overfilling. In addition to these measures, selecting a warehouse or recycling plant strategically located, GHG emissions derived from the transport distances travelled are kept as minimal as possible (Jiménez-Rivero and García-Navarro, 2016).

2.11. Perform GW traceability, from source to final destination (DE11)

Tracking waste materials promotes transparency and quality assurance. Proper traceability of waste involves planning in advance waste carriers and recovery routes, register and keep records of GW amounts and control them. A voluntary initiative, called Tracimat, has been found in the Flemish region (Belgium), aiming to help with C&D waste fractions traceability from January 2016 (Deloitte, 2015). This practice can be performed by the worker appointed for the follow-up of the waste management (see DE2).

2.12. Recycling plant or warehouse strategically located (RE1)

Warehouses and recycling plants store both GW (received from construction sites, public recycling centers, collectors, etc) before processing it, as well as the resulting RG (to be transported to the final customer, e.g. plasterboard manufacturers). Therefore, the location and number of gypsum recycling plants or warehouses are considered crucial for minimizing GHG emissions (see also DE10) and costs, which can incentivize deconstruction companies to prioritize the recycling route or even determine the fate of the waste. Besides, a suitable route should take into consideration to minimize impacts from a social and environmental perspective as well (e.g. local ecosystem disturbance, traffic burden) (Bañas et al., 2010).

2.13. Have an adequate warehouse for GW and RG storage (RE2)

A properly dimensioned and covered storage place should be set up in order to guarantee a constant GW feedstock. Storage areas should be maintained in accordance with the quality assurance system requirements (see RE3) in order to ensure that external contamination and free moisture are prevented (considering the RG quality criteria as detailed in MA1). Experienced gypsum recyclers in the GtoG project reported a coefficient of expansion of 0.4 t/m³ for GW and 0.7 t/m³ for RG (GtoG Project, 2015).

2.14. Operate a quality management system (RE3)

A quality assurance system is an important tool to demonstrate compliance with the RG quality criteria established and to create reliability on the end-of-waste criteria, if existing. For this purpose, an internationally recognized and externally verified quality management system (QMS), such as ISO 9001 or similar may be operated.

Considering the criteria laid down in other industries (The Council of the European Union, 2011; The European Commission, 2013, 2012), a suitable QMS for GW is expected to include the acceptance control of GW, monitoring of the treatment process, monitoring of the quality of the resulting RG, feedback from customers concerning compliance with RG quality, record keeping, review and improvement of the management system as well as training of staff.

2.15. Set clear waste acceptance criteria (RE4)

Waste acceptance criteria (WAC) at the recycling plant or warehouse, also referred as criteria of acceptance (Agrelá et al., 2011), should apply to the waste used as input for gypsum recycling. The acceptance control of waste is commonly performed in compliance with these criteria (The Council of the European Union, 2011; The European Commission, 2013, 2012) WAC should be communicated to customers to develop their management system in line with the WAC, while at the same time facilitating the acceptance control of GW.

2.16. Perform effective sorting operations prior to GW processing (RE5)

The source of GW usually determines the level of impurities. For example, pre-consumer GW requires less sorting than EoL gypsum. The presence of impurities in the accepted waste is typically limited to 2%. Although recycling units are usually equipped with separation technology, a preliminary sorting is typically required in order to minimize the risk of machine breakdown or avoid lower RG quality. Sorting techniques reported by actual gypsum recyclers consist on visual manual sorting (GtoG project, 2013b).

2.17. Prepare a schedule of sampling and test frequencies for each quality criteria parameter (RE6)

Monitoring frequencies should be documented as part of the QMS and should be available for auditing. In addition, sampling results should be recorded, kept for the competent authorities and made available on their request. The sampling procedures and calibration methods shall be also made available for auditing (Villanueva and Eder, 2011; WRAP and BSI, 2013).

2.18. Agree suitable supply contracts between recyclers and manufacturers (RE7)

Supply contracts should be agreed in a collaborative manner. The required information should be obtained, supplied and retained in order to demonstrate, when requested, that RG supplied is destined for appropriate use (WRAP and BSI, 2013).

2.19. Set clear RG quality criteria (MA1)

Existing quality criteria for RG are country-specific and even company-specific. Examples of different quality criteria currently found in the EU are: the RG initial test for recycling plants in Germany (Bundesverband der Gipsindustrie e.V., 2013), PAS 109:2013 in the UK (WRAP and BSI, 2013), as well as other commercial specifications developed by gypsum recyclers, plasterboard manufacturers or Eurogypsum Member Associations. The GtoG project has produced a set of European voluntary guidelines on the RG quality criteria for the gypsum industry, covering technical and toxicological criteria (GtoG project, 2015b).

2.20. Promote plasterboard take-back schemes (MA2)

Extended producer responsibility schemes are adopted in many fields to promote collection and recycling of waste, close the material loop and incentivize ecodesign (Richter and Koppejan, 2015). Increasingly, countries are putting in place “take-back” laws, which require that the manufacturer takes-back the used product at its EoL (Nnorom and Osibanjo, 2008), as recovery and recycling are guaranteed this way. Currently, gypsum products take-back is not mandatory, and thus only voluntary take-back schemes exist (AEA Technology Plc and WRAP, 2006; WRAP, 2006).

2.21. Set a RG reincorporation target (MA3)

The establishment of corporate objectives on environmental sustainability, particularly addressing RG content, promotes closed-loop gypsum recycling. This target may be part of the manufacturer’s corporate social responsibility (GtoG Project, 2015).

2.22. Address the end-of-waste (EoW) status (GE1)

The removal of the waste status can promote the quality of the resulting secondary raw material, which may increase their demand (Delgado et al. 2009). EoW criteria for the production and use of RG from plasterboard waste are only a reality in the UK, governed by the Quality Protocol (WRAP and Environment Agency 2013).

2.23. Availability of suitable closed-top skips (GE2)

Closed-top skips are preferentially recommended for GW storage in order to protect waste from wet weather and minimize free moisture.

3. Methodology: stakeholder consultation

A questionnaire (see Appendix A - Questionnaire) was used to investigate stakeholders' views on the selected best practices to successful management (see Section 2). The online questionnaire was designed and conducted between September and December 2015. Before being launched, the survey was pre-tested in an expert meeting conducted in October 2015 with a group of eight experts, participants of the GtoG project. As a result, the descriptions of the questions were fine-tuned and a new practice was included: "Availability of suitable closed-top skips (GE2)" (see Section 2). In this meeting, the consultation strategy was also defined (i.e. GtoG partners in charge of translating the survey and timeline to collect responses and analyse data). The questionnaire was prepared in English, French, German and Spanish, with the aim to reach the maximum number of responses.

The questionnaire was distributed among 152 stakeholders. Efforts were made to ensure a high response rate. These included a personalized accompanying email, information on the confidentiality clause in the GtoG project consortium agreement and follow-ups of all non-respondents. Respondents were required to rate each practice on a 5-point Likert-type scale, in terms of importance (i.e. influence of the given practice on closing the loop of gypsum products), implementation (i.e. current probability of occurrence of the given practice in respondents' national context) and feasibility (i.e. the extent to which they can be applied or put in practice). Two separate sections formed part of the questionnaire: deconstruction and processing/reincorporation. At the end of each section, space was provided to accommodate comments. The questionnaire also contained a general data part.

A total of 58 responses ($N=58$) were gathered from stakeholders working in gypsum recycling (GR) and non-gypsum recycling (NGR) countries. These stakeholders included manufacturers (16%), construction agents (34%), waste collectors and gypsum recyclers (19%) as well as other stakeholders (researchers (16%) and public institutions and associations (16%)). While 62% of them ($N=36$) perform their activity in GR countries (Belgium, Denmark, France, Netherlands and United Kingdom), 48% ($N=22$) work in NGR countries (Austria, Germany, Greece, Portugal and Spain). Respondents working at European public institutions and associations were considered in the GR countries group. A 38% response rate was achieved.

The analysis, performed using SPSS v23, included descriptive statistics (central tendency: mean, median and dispersion: standard deviation) and the Mann-Whitney U test, a non-parametric test that compares distributions of responses between groups (Harpe, 2015), at 95% confidence interval. In the Mann-Whitney U test the null hypothesis is rejected if the observed p-value is less than the significance level ($\alpha=0.05$). Moreover, Cronbach's alpha coefficient was assessed to check the internal consistency of the scale. The alpha values were 0.942 (importance scale), 0.934 (implementation) and 0.965 (feasibility). As these values are above 0.8, the scale can be considered reliable with our sample (Carmines and Zeller, 1979). Best practices were ranked according to their mean value (M), an approach commonly adopted in construction management research to evaluate Likert-type scales (Ali et al., 2013; Lu and Yuan, 2010; Poon et al., 2001; Villoria Saez et al., 2013; Wang et al., 2010). M can be expressed as follows: $M = \frac{\sum_{y=1}^5 N_{xy} S_y}{\sum_{y=1}^5 N_{xy}}$, where N_{xy} is the number of stakeholders that chose the y th score (S_y) for the x th best practice and S_y is the score given by stakeholders for each best practice.

The identification of practices commonly applied in GR but not yet adopted in NGR countries permitted to propose fundamental practices to enable gypsum recycling. The cut-off mean value was set at 4.00. Moreover, current implementation above 70% in GR countries was required (see Fig. 2) in order to be considered a fundamental practice.

4. Results and discussion

Table 2 summarizes the analysis on the importance given by stakeholders (see Section 3 for details on the selected statistics). Practices are ranked (from highest to lowest mean) according to the mean value on importance from GR countries, due to their experience in leading approaches for the achievement of an improved deconstruction-recycling value chain. The higher the mean value, the higher the stakeholders valued

the practice. In addition, results from the Mann-Whitney U test are shown, which are useful to determine statistical difference between how the stakeholders working in GR and NGR countries view the selected practices.

Table 2. Results of the questionnaire survey on the importance of best practices

No.	GR countries				NGR countries				Mann-Whitney		
	M	SD	Mdn	Rank	No.	M	SD	Mdn	Rank	Z	p
RE4	4.67	0.48	5.00	1	RE4	4.13	1.30	5.00	6	-0.953	0.341
DE7	4.64	0.90	5.00	2	DE7	4.25	1.00	5.00	4	-1.591	0.112
RE5	4.58	0.58	5.00	3	RE5	4.07	1.07	4.00	7	-1.699	0.089
RE2	4.48	0.51	4.00	4	RE2	3.94	1.18	4.00	12	-1.318	0.187
MA1	4.48	0.81	5.00	5	MA1	4.19	1.28	5.00	5	-0.336	0.737
RE1	4.39	0.66	4.00	6	RE1	3.88	1.36	4.00	13	-0.938	0.348
DE2	4.32	0.57	4.00	7	DE2	4.00	1.13	4.00	9	-0.611	0.541
DE3	4.25	0.72	4.00	8	DE3	3.69	1.14	4.00	17	-1.524	0.128
DE5	4.23	0.75	4.00	9	DE5	3.94	1.37	4.00	11	-0.682	0.495
RE3	4.23	0.92	4.00	10	RE3	3.80	1.12	4.00	14	-0.728	0.467
DE1	4.21	0.85	4.00	11	DE1	4.33	0.72	4.00	2	-0.321	0.748
DE11	4.19	1.03	4.00	12	DE11	2.93	1.28	3.00	23	-2.923	0.003
DE4	4.09	1.06	4.00	13	DE4	3.94	1.06	4.00	10	-0.516	0.606
DE9	4.05	1.09	4.00	14	DE9	3.69	0.63	4.00	18	-0.718	0.473
DE10	4.05	0.90	4.00	15	DE10	3.75	1.14	4.00	16	-0.866	0.387
RE7	4.05	1.05	4.00	16	RE7	4.40	1.18	4.00	1	-0.792	0.429
MA3	4.00	1.00	4.00	17	MA3	3.44	1.41	3.50	21	-1.163	0.245
RE6	3.96	0.82	4.00	18	RE6	4.07	0.83	4.00	8	-0.512	0.608
MA2	3.95	0.95	4.00	19	MA2	4.27	1.10	5.00	3	-1.267	0.205
DE8	3.95	1.24	4.00	20	DE8	3.56	1.15	4.00	19	-1.190	0.234
GE1	3.85	1.09	4.00	21	GE1	3.42	0.96	4.00	22	-1.564	0.118
GE2	3.71	1.20	4.00	22	GE2	3.45	1.15	3.50	20	-0.858	0.391
DE6	3.41	1.33	4.00	23	DE6	3.75	1.00	3.50	15	-0.567	0.571

Recycling (GR) countries: BE, UK, FR, NL, DK. Non-recycling (NGR) countries: AU, DE, GR, SP, PT

4.1. Main differences between respondents in GR and NGR countries

Results from NGR countries were much more spread out (*SD* above 1 in most of the cases) than those from GR countries (*SD* below 1 in most of the cases). These differences could be attributed to the different level of information on GW management in NGR countries, which did not allow greater consensus between stakeholders. It is interesting to note that the least valued practices in GR countries coincide with highly variable opinions among stakeholders (see standard deviation, importance column, in Table 2). We refer to four practices: “Effective planning of GW capture systems” (DE8), “Address the end-of-waste (EoW) status” (GE1), “Availability of suitable closed-top skips” (GE2) and “Appointment of trained workers” (DE6). Fig. 1 and Fig. 2 provide further insight into this variability in terms of importance, showing that quite different perceptions exist between GR and NGR countries (Fig. 1) and stakeholders (Fig. 2).




Fig. 1. Results of the questionnaire survey on the importance of practices. Recycling (GR) countries: BE, UK, FR, NL, DK. Non-recycling (NGR) countries: AU, DE, GR, SP, PT




Fig. 1. Importance given by different stakeholders in GR countries (BE, UK, FR, NL, DK) and NGR countries (AU, DE, GR, SP, PT)

Only one practice, “Perform GW traceability, from source to final destination” (DE11), demonstrated a significant difference in terms of importance between GR ($M=4.19$, $SD=1.03$) and NGR countries ($M=2.93$, $SD=1.28$), as shown in Table 2. It is interesting to note that DE11 presents the higher proportion of respondents (40%) that scored it below 3 in NGR countries, which compares well with the results revealed by the Mann-Whitney U test. By contrast, 81% of GR stakeholders perceived traceability as highly or extremely important (see Fig. 1). This could be because traceability principles are not yet embraced by NGR countries and, therefore, NGR stakeholders are not familiar with tracking waste materials to the final destination. In addition, voluntary traceability tools and initiatives have already emerged in GR countries (e.g. Tracimat in Belgium or SmartWaste in the UK, as detailed in Section 2).

In the NGR stakeholders’ responses, two practices are viewed as promising to improve the value chain: “Agree suitable supply contracts between recyclers and manufacturers” (RE7) and “Promote plasterboard take-back schemes” (MA2), which ranked first and third respectively (while for GR countries, these practices ranked 16 and 19 respectively, see Table 2 for further details). With regard to MA2, these results may indicate that stakeholders in NGR countries rely on the concept of the extended producer responsibility in order to

enhance gypsum waste management. The reason for the score of RE7 in NGR countries may have something to do with the lack of nearby gypsum recyclers in these countries and therefore the impossibility of agreeing such contracts.

4.2. *Proposed fundamental best practices to enable a circular economy for gypsum products*

Three best practices are identified as fundamental (see Section 3 for details on the application of the criteria) to promote a circular economy for gypsum products: “Set clear waste acceptance criteria” (RE4), “Perform on-site segregation of GW” (DE7) and “Set clear RG quality criteria” (MA1).

4.2.1. Set clear waste acceptance criteria

“Set clear waste acceptance criteria” (RE4) was the highest rated practice in terms of importance for an efficient closed-loop supply chain (Table 2). This high score can be explained by the decisive role of these criteria on the accept or reject decision by the recycler. Moreover, stakeholders should follow such criteria in order to adequately collect (e.g. on-site collection, performed by construction agents) and supply (e.g. waste collectors, transfer stations) the waste. This practice is considered to be extremely important (i.e. score of five) by around 60% of respondents in both groups of countries. Surprisingly, recycling agents rated RE4 below the average ($M=4.56$; $SD=0.53$). This may be due to the confidence of recyclers on their current waste acceptance criteria, along with the appointment of skilled workers to perform hand-sorting at the recycling plant. As can be observed in Fig. 3, RE4 is implemented in 80% of the cases in GR countries ($M=4.00$; $SD=1.11$), while it is not a usual practice in NGR ones ($M=2.23$; $SD=1.42$, see Table A.1. in Appendix A for further details). This practice demonstrates a statistically significant difference between both group of countries in terms of implementation ($Z=-3.29$; $p=0.001$) and feasibility ($Z=-4.23$; $p=0.000$).

4.2.2. Perform on-site segregation of gypsum waste

“Perform on-site segregation of GW” (DE7) ranked second ($M=4.64$; $SD=0.90$) in GR countries (see Table 2). This practice is considered to be extremely important by 82% of respondents in GR countries (Fig. 1). In these GR countries, construction agents valued this segregation below the rest of stakeholders ($M=4.46$; $SD=1.13$). One possible explanation is that construction agents rely on subsequent segregation in a transfer station. As Wang et al. (2010) found, factors such as cost considerations or managerial issues might impact their response. However, mixed waste collection on-site does not benefit the recyclability of the gypsum fraction. In terms of implementation, while 78% commonly applied DE7 in GR countries, only 50% implement it in NGR countries (Fig. 3). This percentage compares well with the value obtained by Villoria Saez et al. in a survey conducted in 2012 in Spain (NGR country), in which 43% of construction agents did not claim to practice source separation. As a result, the segregated GW is consequently landfilled in NGR countries, as there are no gypsum recyclers nearby. The mean value obtained for implementation in these NGR countries ($M=3.06$; $SD=1.24$) compares well with the value obtained by Lu and Yuan in the survey conducted in Shenzhen (China) in 2008 ($M=3.00$; $SD=0.62$). This segregation of gypsum is usually performed in order to avoid contamination of concrete (Barbudo et al., 2012; Silva et al., 2014; Tovar-Rodríguez et al., 2013), and represents a lost opportunity to produce recycled gypsum. While more than 80% of respondents in GR countries perceived this on-site segregation as feasible ($M=4.64$; $SD=0.90$), only 56% agreed with this in NGR countries ($M=3.13$; $SD=1.45$) (Fig. 3 and Table A.1. in Appendix A). This can be explained by the deep-rooted tradition of on-site mixed waste collection in these contexts, which produce a significant difference between countries regarding the implementation ($Z=-2.84$; $p=0.005$) and feasibility ($Z=-4.00$; $p=0.000$) of DE7.

4.2.3. Set clear recycled gypsum quality criteria

“Set clear RG quality criteria” (MA1) ranked fifth in both group of countries (Table 2) and is regarded as extremely important by around 60% of stakeholders in both group of countries (Fig. 1). Interestingly, all manufacturers in GR countries considered MA1 as extremely important, which compares well with the increasing interest of developing quality criteria documents in countries such as Germany and the UK, as well

as the European guidelines produced within the GtoG project (Bundesverband der Gipsindustrie e.V., 2013; GtoG project, 2015b; WRAP and BSI, 2013). The Mann-Whitney U test revealed a significant difference between GR and NGR respondents with regard to the implementation of MA1 ($Z=-2.86$; $p=0.004$).




Fig. 2. Rate of respondents that highly implement the practice (I) and perceive it as highly feasible (F), above 4 in the rating scale. Recycling (GR) countries: BE, UK, FR, NL, DK. Non-recycling (NGR) countries: AU, DE, GR, SP, PT.

1 5. Conclusions

2 Once end-of-life (EoL) construction products are generated, adopted practices by stakeholders play a central
 3 role in determining their fate. Best practices on waste management, if properly organized and implemented,
 4 benefit the waste hierarchy and promote a circular economy of products, which prevents losses of potential
 5 secondary raw materials. In this investigation, we have proposed a set of best practices for the management of
 6 EoL gypsum in a circular economy. Moreover, we have examined how the best practices are viewed by
 7 stakeholders working in gypsum recycling (GR) and non-recycling (NGR) countries. The survey conducted
 8 targeted European stakeholders of the deconstruction-recycling value chain.

9 Three best practices are identified as fundamental to enable a circular economy for gypsum products:
10 “Perform an on-site segregation of gypsum waste”, “Set clear waste acceptance criteria” and “Set clear RG
11 quality criteria”. At present, on-site segregation of gypsum waste is only commonly applied by half of
12 stakeholders in NGR countries (mainly to avoid EoL concrete contamination, then gypsum waste ends up in
13 landfills due to the lack of gypsum recycling plants in NGR countries). This on-site segregation of gypsum
14 waste enhances the generation of recyclable gypsum waste (i.e. in compliance with the waste acceptance
15 criteria) and thus the production of recycled gypsum that complies with the agreed recycled gypsum quality
16 criteria. Once these fundamental practices are in place in a region, the rest of best practices aim to provide
17 guidance for stakeholders to enable informed decisions to be made regarding adopted practices during the EoL
18 stage. Although this study focused on EoL gypsum in the European Union, the best practices here identified
19 are valuable for replication in other regions and waste fractions.

20 **Acknowledgement**

21 This study has been performed under the framework of the GtoG project, supported by the European
22 Commission – DG Environment through the Life + programme; under contract number LIFE11
23 ENV/BE/001039. We wish to thank the surveyed stakeholders for their time and support. The article has been
24 prepared during the research stay of Ana Jiménez at TU Delft, from February to April 2016, granted by the
25 “XVI Convocatoria de ayudas del Consejo Social para el Fomento de la Internacionalización de Doctorados”,
26 Universidad Politécnica de Madrid. We would also like to thank Dr. M.L. Maaike Beliën for the writing
27 assistance.

30 **Appendix A. Supplementary data**

31 Supplementary data associated with this article can be found, in the online version, at
32 <https://doi.org/10.1016/j.jclepro.2017.05.068>.

34 **References**

- 36 AEA Technology Plc, WRAP, 2006. Review of Plasterboard Material Flows and Barriers to Greater Use of
37 Recycled Plasterboard. Available at:
38 [http://www.wrap.org.uk/sites/files/wrap/PBD0004%20Plasterboard%20material%20flows%20report.p](http://www.wrap.org.uk/sites/files/wrap/PBD0004%20Plasterboard%20material%20flows%20report.pdf)
39 [df](http://www.wrap.org.uk/sites/files/wrap/PBD0004%20Plasterboard%20material%20flows%20report.pdf) (accessed 08.05.17).
- 40 Agrela, F., Sanchez De Juan, M., Ayuso, J., Geraldes, V.L., Jimenez, J.R., 2011. Limiting properties in the
41 characterisation of mixed recycled aggregates for use in the manufacture of concrete. *Construction and*
42 *Building Materials* 25, 3950–3955. doi:10.1016/j.conbuildmat.2011.04.027
- 43 Ajayi, S.O., Oyedele, L.O., Bilal, M., Akinade, O.O., Alaka, H.A., Owolabi, H.A., Kadiri, K.O., 2015. Waste
44 effectiveness of the construction industry : Understanding the impediments and requisites for
45 improvements. *Resources, Conservation & Recycling* 102, 101–112.
46 doi:10.1016/j.resconrec.2015.06.001
- 47 Ali, H.A.E.M., Al-Sulaihi, I.A., Al-Gahtani, K.S., 2013. Indicators for measuring performance of building
48 construction companies in Kingdom of Saudi Arabia. *Journal of King Saud University - Engineering*
49 *Sciences* 25, 125–134. doi:10.1016/j.jksues.2012.03.002
- 50 Antink, R., Garrigan, C., Bonetti, M., Westaway, R., 2014. Greening the Building Supply Chain. UNEP
51 Sustainable Buildings and Climate Initiative. United Nations Environment Programme. Job Number:
52 DTI/1753/PA. Available at: <http://staging.unep.org/sbci/> (accessed 08.05.17).
- 53 Baniyas, G., Achillas, C., Vlachokostas, C., Moussiopoulos, N., Tarsenis, S., 2010. Assessing multiple criteria
54 for the optimal location of a construction and demolition waste management facility. *Building and*
55 *Environment* 45, 2317–2326. doi:10.1016/j.buildenv.2010.04.016

- 56 Barbudo, A., Galvín, A.P., Agrela, F., Ayuso, J., Jiménez, J.R., 2012. Correlation analysis between sulphate
57 content and leaching of sulphates in recycled aggregates from construction and demolition wastes.
58 *Waste Management* 32, 1229–35. doi:10.1016/j.wasman.2012.02.005
- 59 Barczak, G., Kahn, K.B., 2012. Identifying new product development best practice. *Business Horizons* 55,
60 293–305. doi:10.1016/j.bushor.2012.01.006
- 61 Beamon, B.M., Fernandes, C., 2004. Supply-chain network configuration for product recovery. *Production*
62 *Planning & Control* 15, 270–281. doi:10.1080/09537280410001697701
- 63 Begum, R.A., Siwar, C., Pereira, J.J., Jaafar, A.H., 2009. Attitude and behavioral factors in waste
64 management in the construction industry of Malaysia. *Resources, Conservation and Recycling* 53, 321–
65 328. doi:10.1016/j.resconrec.2009.01.005
- 66 Benyus, J.M., 2002. *Biomimicry: Innovation Inspired by Nature*. Harper Perennial.
- 67 Buildings Performance Institute Europe (BPIE), 2011. Europe’s buildings under the microscope. Available
68 at: http://bpie.eu/wp-content/uploads/2015/10/HR_EU_B_under_microscope_study.pdf (accessed
69 08.05.17).
- 70 Bundesverband der Gipsindustrie e.V., 2013. Recycled gypsum (RC-gypsum). Initial test for recycling
71 plants, quality management, quality requirements and analysis methods.
- 72 Calvo, N., Varela-Candamio, L., Novo-Corti, I., 2014. A dynamic model for construction and demolition
73 (C&D) waste management in Spain: Driving policies based on economic incentives and tax penalties.
74 *Sustainability* 6, 416–435. doi:10.3390/su6010416
- 75 Carmines, E.G., Zeller, R.A., 1979. Reliability and validity assessment. *Quantitative Applications in the*
76 *Social Sciences*. doi:10.1037/018269
- 77 Chini, A., Bruening, S., 2003. Deconstruction and materials reuse in the United States. *The Future of*
78 *Sustainable Construction* 1–22. ISBN: 1-886431-09-4.
- 79 CIB International Council for Research and Innovation in Building and Construction, 2000. Overview of
80 Deconstruction in Selected Countries (CIB Publication 252), Edited by Charled J.Kibert and Abdol R.
81 Chini. Task Group 39: Deconstruction. ISBN 0-9643886-3-4.
- 82 CIB International Council for Research and Innovation in Building and Construction, 2014. Barriers for
83 Deconstruction and Reuse / Recycling of Construction Materials. CIB Publication 397. Available at:
84 <http://site.cibworld.nl/db/publication/browserecord.php?action=browse&-recid=1370> (accessed
85 08.05.17).
- 86 del Río Merino, M., Izquierdo Gracia, P., Weis Azevedo, I.S., 2010. Sustainable construction: construction
87 and demolition waste reconsidered. *Waste management & research : the journal of the International*
88 *Solid Wastes and Public Cleansing Association, ISWA* 28, 118–129. doi:10.1177/0734242X09103841
- 89 Delgado, L., Sofia-Catarino, A., Eder, P., Litten, D., Luo, Z., Villanueva, A., 2009. End of waste criteria.
90 Final Report. doi:10.2791/28650
- 91 Deloitte, 2015. Screening template for Construction and Demolition Waste management in Belgium.
92 Available at:
93 http://ec.europa.eu/environment/waste/studies/deliverables/CDW_Belgium_Factsheet_Final.pdf
94 (accessed 08.05.17).
- 95 Eleftheriadis, R.J., Myklebust, O., 2015. Benchmark and Best Practice of IFaCOM Industrial Demonstrators.
96 *Procedia CIRP* 33, 311–314. doi:10.1016/j.procir.2015.06.062
- 97 Ellen MacArthur Foundation, 2016. Towards a Circular Economy - Economic and Business Rationale for an
98 Accelerated Transition. Available at:
99 [https://www.ellenmacarthurfoundation.org/assets/downloads/TCE_Ellen-MacArthur-Foundation-9-](https://www.ellenmacarthurfoundation.org/assets/downloads/TCE_Ellen-MacArthur-Foundation-9-Dec-2015.pdf)
100 [Dec-2015.pdf](https://www.ellenmacarthurfoundation.org/assets/downloads/TCE_Ellen-MacArthur-Foundation-9-Dec-2015.pdf) (accessed 08.05.17).
- 101 European Commission, 2015. Communication from the Commission to the European Parliament, the

- 102 Council, the European Economic and Social Committee and the Committee of the Regions. Closing the
103 loop - An EU action plan for the Circular Economy. Available at: [http://eur-lex.europa.eu/legal-
content/en/TXT/?uri=CELEX%3A52015DC0614](http://eur-lex.europa.eu/legal-
104 content/en/TXT/?uri=CELEX%3A52015DC0614) (accessed 08.05.17).
- 105 European Commission (DG ENV), 2011. Service Contract on Management of Construction and Demolition
106 Waste - SR1. Final Report Task 2. A project under the Framework contract ENV.G.4/FRA/2008/0112.
107 Available at: http://ec.europa.eu/environment/waste/pdf/2011_CDW_Report.pdf (accessed 20.03.17).
- 108 European Committee for Standardization (CEN), 2013. EN 15804:2012+A1:2013. Sustainability of
109 construction works - Environmental product declarations - Core rules for the product category of
110 construction products.
- 111 European Parliament and the Council of the European Union, 2008. Directive 2008/98/EC of the European
112 Parliament and of the Council of 19 November 2008 on waste and repealing certain Directives.
113 Available at: [http://eur-
lex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ:L:2008:312:0003:0030:en:PDF](http://eur-
114 lex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ:L:2008:312:0003:0030:en:PDF) (accessed 20.03.17).
- 115 Faniran, O.O., Caban, G., 1998. Minimizing waste on construction project sites. *Engineering, Construction
116 and Architectural Management* 5, 182–188. doi:10.1108/eb021073
- 117 Farel, R., Yannou, B., Bertoluci, G., 2013. Finding best practices for automotive glazing recycling: A
118 network optimization model. *Journal of Cleaner Production* 52, 446–461.
119 doi:10.1016/j.jclepro.2013.02.022
- 120 Formoso, C.T., M-Asce Soibelman, L., De Cesare, C., Isatto, E.L., 2002. Material waste in building industry:
121 main causes and prevention. *Journal of Construction Engineering and Management* 128, 316–326.
122 doi:10.1061/~ASCE!0733-9364~2002!128:4~316!
- 123 GtoG project, 2015a. DC1. Report on best practice indicators for deconstruction, recycling and
124 reincorporation LIFE11 ENV/BE/001039. Available at:
125 http://ec.europa.eu/environment/life/news/newsarchive2015/documents/20150715_gtog.pdf (accessed
126 20.03.17).
- 127 GtoG project, 2015b. DC2: Protocol of action B2.2: Quality criteria for recycled gypsum, technical and
128 toxicological parameters LIFE11 ENV/BE/001039. Available at:
129 [http://gypsumtogypsum.org/documents/quality-criteria-for-recycled-gypsum-technical-and-
toxicological-parameters.pdf](http://gypsumtogypsum.org/documents/quality-criteria-for-recycled-gypsum-technical-and-
130 toxicological-parameters.pdf) (accessed 20.03.17).
- 131 GtoG project, 2013. Life+ Gypsum to Gypsum (GtoG) project “From production to recycling: a circular
132 economy for the European Gypsum Industry with the Demolition and Recycling Industry” LIFE11
133 ENV/BE/001039. Available at:
134 [http://ec.europa.eu/environment/life/project/Projects/index.cfm?fuseaction=search.dspPage&n_proj_id
=4191](http://ec.europa.eu/environment/life/project/Projects/index.cfm?fuseaction=search.dspPage&n_proj_id
135 =4191) (accessed 20.03.17).
- 136 GtoG Project, 2015c. DA2: Inventory of best practices LIFE11 ENV/BE/001039. Available at:
137 <http://gypsumtogypsum.org/documents/da2-inventory-of-best-practices.pdf> (accessed 20.03.17).
- 138 Harpe, S.E., 2015. How to analyze Likert and other rating scale data. *Currents in Pharmacy Teaching and
139 Learning* 7, 836–850. doi:10.1016/j.cptl.2015.08.001
- 140 Heibeler, R., Kelly, T.B., Kettelman, C., 1998. *Best Practices—Building Your Business with Customer-
141 Focused Solutions*. Simon & Schuster, New York.
- 142 HISER project - H2020 under agreement No. 642085, n.d. Demolition case study: business-as-usual in
143 Flanders. HISER Project, News.. Available at:
144 [http://www.hiserproject.eu/index.php/component/content/article?id=117:demolition-case-study-
business-as-usual-in-flanders](http://www.hiserproject.eu/index.php/component/content/article?id=117:demolition-case-study-
145 business-as-usual-in-flanders) (accessed 20.03.17).
- 146 Hjelm, O., Van Der Sloot, H. a., Comans, R.N.J., Wahlström, M., 2013. EoW criteria for waste-derived
147 aggregates. *Waste and Biomass Valorization* 4, 809–819. doi:10.1007/s12649-013-9261-8
- 148 Hurley, J.W., 2003. Valuing the Pre-Demolition Audit Process. CIB Report 287. Florida, USA. Available at:
149 <http://cibw117.com/europe/valuing-the-pre-demolition-audit-process/> (accessed 08.05.17).

- 150 Jiménez-Rivero, A., García-Navarro, J., 2017. Exploring factors influencing post-consumer gypsum
151 recycling and landfilling in the European Union. *Resources, Conservation and Recycling* 116, 116–123.
152 doi:10.1016/j.resconrec.2016.09.014
- 153 Jiménez-Rivero, A., García-Navarro, J., 2016. Indicators to Measure the Management Performance of End-
154 of-Life Gypsum: From Deconstruction to Production of Recycled Gypsum. *Waste and Biomass*
155 *Valorization* 7, 913–927. doi:10.1007/s12649-016-9561-x
- 156 Jiménez Rivero, A., Sathre, R., García Navarro, J., 2016. Life cycle energy and material flow implications of
157 gypsum plasterboard recycling in the European Union. *Resources, Conservation and Recycling* 108,
158 171–181. doi:10.1016/j.resconrec.2016.01.014
- 159 Kourmpanis, B., Papadopoulos, a., Moustakas, K., Stylianou, M., Haralambous, K.J., Loizidou, M., 2008.
160 Preliminary study for the management of construction and demolition waste. *Waste Management &*
161 *Research* 26, 267–275. doi:10.1177/0734242X07083344
- 162 Kurdve, M., Shahbazi, S., Wendin, M., Bengtsson, C., Wiktorsson, M., 2014. Waste flow mapping to
163 improve sustainability of waste management: a case study approach. *Journal of Cleaner Production* 98,
164 304–315. doi:10.1016/j.jclepro.2014.06.076
- 165 Llatas, C., 2011. A model for quantifying construction waste in projects according to the European waste list.
166 *Waste management (New York, N.Y.)* 31, 1261–76. doi:10.1016/j.wasman.2011.01.023
- 167 Lönngren, H.-M., Rosenkranz, C., Kolbe, H., 2010. Aggregated construction supply chains: success factors
168 in implementation of strategic partnerships. *Supply Chain Management: An International Journal* 15,
169 404–411. doi:10.1108/13598541011068297
- 170 Lu, W., Huang, G.Q., Li, H., 2011. Scenarios for applying RFID technology in construction project
171 management. *Automation in Construction* 20, 101–106. doi:10.1016/j.autcon.2010.09.007
- 172 Lu, W., Yuan, H., 2010. Exploring critical success factors for waste management in construction projects of
173 China. *Resources, Conservation and Recycling* 55, 201–208. doi:10.1016/j.resconrec.2010.09.010
- 174 Mansar, S.L., Reijers, H. a., 2005. Best practices in business process redesign: Validation of a redesign
175 framework. *Computers in Industry* 56, 457–471. doi:10.1016/j.compind.2005.01.001
- 176 McDonough, W., Braungart, M., 2002. Design for the triple top line: New tools for sustainable commerce.
177 *Corporate Environmental Strategy* 9, 251–258. doi:10.1016/S1066-7938(02)00069-6
- 178 Ministerio de la Presidencia, 2008. Real Decreto 105/2008, de 1 de febrero, por el que se regula la
179 producción y gestión de los residuos de construcción y demolición. Available at:
180 <https://www.boe.es/buscar/act.php?id=BOE-A-2008-2486> (accessed 08.05.17).
- 181 Nnorom, I.C., Osibanjo, O., 2008. Overview of electronic waste (e-waste) management practices and
182 legislations, and their poor applications in the developing countries. *Resources, Conservation and*
183 *Recycling* 52, 843–858. doi:10.1016/j.resconrec.2008.01.004
- 184 Poon, C.S., Yu, A.T.W., Ng, L.H., 2001. On-site sorting of construction and demolition waste in Hong
185 Kong. *Resources, Conservation and Recycling* 32, 157–172. doi:10.1016/S0921-3449(01)00052-0
- 186 Richter, J.L., Koppejan, R., 2015. Extended producer responsibility for lamps in Nordic countries: best
187 practices and challenges in closing material loops. *Journal of Cleaner Production* 1–13.
188 doi:10.1016/j.jclepro.2015.06.131
- 189 Rose, K. a, Sable, S., Deangelis, D.L., Yurek, S., Trexler, J.C., Graf, W., Reed, D.J., 2015. Proposed best
190 modeling practices for assessing the effects of ecosystem restoration on fish. *Ecological Modelling* 300,
191 12–29. doi:10.1016/j.ecolmodel.2014.12.020
- 192 Rossi, M., Terzi, S., Taisch, M., 2012. Engineering and Design Best Practices in New Product Development :
193 an Empirical Research. *Procedia CIRP* 21, 2. doi:10.1016/j.procir.2014.03.184
- 194 Shen, L.Y., Tam, V.W.Y., 2002. Implementation of environmental management in the Hong Kong
195 construction industry. *International Journal of Project Management* 20, 535–543. doi:10.1016/S0263-

- 196 7863(01)00054-0
- 197 Silva, R.V., de Brito, J., Dhir, R.K., 2014. Properties and composition of recycled aggregates from
198 construction and demolition waste suitable for concrete production. *Construction and Building*
199 *Materials* 65, 201–217. doi:10.1016/j.conbuildmat.2014.04.117
- 200 Silvestre, J.D., de Brito, J., Pinheiro, M.D., 2014. Environmental impacts and benefits of the end-of-life of
201 building materials – calculation rules, results and contribution to a “cradle to cradle” life cycle. *Journal*
202 *of Cleaner Production* 66, 37–45. doi:10.1016/j.jclepro.2013.10.028
- 203 Singapore Government, n.d. Guidelines for Pre-Demolition Audit, Sequential Demolition and Site Waste
204 Management Plan. Available at:
205 https://www.bca.gov.sg/SustainableConstruction/others/sc_demoproto.pdf (accessed 08.05.17).
- 206 Singapore Government, n.d. Demolition protocol. Available at:
207 https://www.bca.gov.sg/SustainableConstruction/sc_demolition.html (accessed 08.05.17).
- 208 Stahel, W.R., 2010. *The performance economy*, Second ed. ed. Palgrave Macmillan. ISBN: 978-0-230-
209 58466-2.
- 210 Szulanski, G., 1996. Exploring Internal Stickiness: Impediments To the Transfer of Best Practice Within the
211 Firm. *Strategic Management Journal* 17, 27–43. doi: 10.1002/smj.4250171105
- 212 Tam, V.W.Y., 2008. On the effectiveness in implementing a waste-management-plan method in
213 construction. *Waste Management* 28, 1072–1080. doi:10.1016/j.wasman.2007.04.007
- 214 Tam, V.W.Y., Fung, I.W.H., Sing, M.C.P., Ogunlana, S.O., 2014. Best practice of prefabrication
215 implementation in the Hong Kong public and private sectors. *Journal of Cleaner Production*.
216 doi:10.1016/j.jclepro.2014.09.045
- 217 The Council of the European Union, 2011. Council Regulation (EU) No 333/2011 of 31 March 2011
218 establishing criteria determining when certain types of scrap metal cease to be waste under Directive
219 2008/98/EC of the European Parliament and of the Council. Available at: [http://eur-lex.europa.eu/legal-](http://eur-lex.europa.eu/legal-content/EN/TXT/?uri=celex:32011R0333)
220 [content/EN/TXT/?uri=celex:32011R0333](http://eur-lex.europa.eu/legal-content/EN/TXT/?uri=celex:32011R0333) (accessed 08.05.17).
- 221 The European Commission, 2013. Commission Regulation (EU) No 715/2013 of 25 July 2013 establishing
222 criteria determining when copper scrap ceases to be waste under Directive 2008/98/EC of the European
223 Parliament and of the Council L201/14-L201/20. Available at: [http://eur-lex.europa.eu/legal-](http://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32013R0715)
224 [content/EN/TXT/?uri=CELEX%3A32013R0715](http://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32013R0715) (accessed 08.05.17).
- 225 The European Commission, 2012. Commission Regulation (EU) No 1179/2012 of 10 December 2012
226 establishing criteria determining when glass cullet ceases to be waste under Directive 2008/98/EC of
227 the European Parliament and of the Council. Available at: [http://eur-lex.europa.eu/legal-](http://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32012R1179)
228 [content/EN/TXT/?uri=CELEX%3A32012R1179](http://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32012R1179) (accessed 08.05.17).
- 229 Tovar-Rodríguez, G., Barra, M., Pialarissi, S., Aponte, D., Vázquez, E., 2013. Expansion of mortars with
230 gypsum contaminated fine recycled aggregates. *Construction and Building Materials* 38, 1211–1220.
231 doi:10.1016/j.conbuildmat.2012.09.059
- 232 Tukker, A., Groot, H. De, Simons, I., Wieggersma, S., 1999. *Chemical Recycling of Plastics Waste (PVC and*
233 *other resins)*. Delft, the Netherland. TNO- 7–107. doi:STB-99-55 Final
- 234 Villanueva, A., Delgado, L., Luo, Z., Eder, P., Catarino, A.S., Litten, D., 2010. Study on the selection of
235 waste streams for end-of-waste assessment. Final Report. doi:10.2791/41968
- 236 Villanueva, A., Eder, P., 2011. End-of-waste criteria for waste paper: Technical proposals.
237 doi:10.2791/57814
- 238 Villoria Saez, P., Del Río Merino, M., San-Antonio González, A., Porrás-Amores, C., 2013. Best practice
239 measures assessment for construction and demolition waste management in building constructions.
240 *Resources, Conservation and Recycling* 75, 52–62. doi:10.1016/j.resconrec.2013.03.009
- 241 Wang, J., Yuan, H., Kang, X., Lu, W., 2010. Critical success factors for on-site sorting of construction

- 242 waste: A china study. *Resources, Conservation and Recycling* 54, 931–936.
243 doi:10.1016/j.resconrec.2010.01.012
- 244 Ward, J.L., 1997. Growing the Family Business: Special Challenges and Practices. *Family Business Review*
245 10, 323–338. doi:10.1111/j.1741-6248.1997.00323.x
- 246 Wilson, D.C., Rodic, L., Cowing, M.J., Velis, C.A., Whiteman, A.D., Scheinberg, A., Vilches, R.,
247 Masterson, D., Stretz, J., Oelz, B., 2014. “Wasteaware” benchmark indicators for integrated sustainable
248 waste management in cities. *Waste Management* 35, 329–342. doi:10.1016/j.wasman.2014.10.006
- 249 WRAP, 2011. WRAP Site Waste Management Plan Template version 2.3. Available at:
250 <http://swmptracker.wrap.org.uk/> (accessed 08.05.17).
- 251 WRAP, 2007. Capture of waste plasterboard on construction sites. Available at:
252 <http://www.wrap.org.uk/sites/files/wrap/Cost%20effective%20solutions%20report%20-%20final.pdf>
253 (accessed 08.05.17).
- 254 WRAP, 2006. Plasterboard Case Study British Gypsum take-back scheme. Available at:
255 [http://www.wrap.org.uk/sites/files/wrap/Case%20study%20-](http://www.wrap.org.uk/sites/files/wrap/Case%20study%20-%20Implementation%20of%20plasterboard%20waste%20take-back%20scheme%20on%20two%20projects1.pdf)
256 [%20Implementation%20of%20plasterboard%20waste%20take-](http://www.wrap.org.uk/sites/files/wrap/Case%20study%20-%20Implementation%20of%20plasterboard%20waste%20take-back%20scheme%20on%20two%20projects1.pdf)
257 [back%20scheme%20on%20two%20projects1.pdf](http://www.wrap.org.uk/sites/files/wrap/Case%20study%20-%20Implementation%20of%20plasterboard%20waste%20take-back%20scheme%20on%20two%20projects1.pdf) (accessed 08.05.17).
- 258 WRAP, BSI, 2013. PAS 109:2013. Specification for the production of reprocessed gypsum from waste
259 plasterboard. Available at: [http://www.wrap.org.uk/sites/files/wrap/PAS109 \(2013\).pdf](http://www.wrap.org.uk/sites/files/wrap/PAS109%20(2013).pdf) (accessed
260 20.03.17).
- 261 Zairi, M., 1997. Business process management: a boundaryless approach to modern competitiveness.
262 *Business Process Management Journal* 3, 64–80. doi: 10.1108/14637159710161585
- 263 Zutshi, A., Creed, A., 2014. An international review of environmental initiatives in the construction sector.
264 *Journal of Cleaner Production* 98, 92–106. doi:10.1016/j.jclepro.2014.06.077
- 265